



Goodall Super Kemflex® Chemical Transfer Hose

Available for the oilfield industry.

Goodall's Super Kemflex® Chemical Transfer Hose provides the ultimate in kink and crush resistance, flexibility, ease of handling and performance with the aggressive chemicals used during fracturing operations.

- 200 psi working pressure
- Dual plastic monofilament helixes
- UHMPE (Ultra High Molecular Weight Polyethylene) tube
- 4:1 safety factor
- Full vacuum rating
- Braided construction

Goodall's Super Kemflex® is an investment in superior performance and safety.

The recommended fittings for this product are stainless steel (always confirm chemical compatibility) using crimped ferrules.

Specifications

Nominal Bore mm	I.D.		O.D.		Maximum Working Pressure		Minimum Burst Pressure		Vacuum Rating		Minimum Bend Radius		Weight		Standard Length	
	in.	mm	in.	mm	bar	psi	bar	psi	mm	in., HG	mm	in.	kg/m	lb./ft.	mm	ft.
25.4	1	40.39	1.59	40.39	13.79	200	55.16	800	736.6	29	101.6	4	0.76	0.51	30.48	100
31.75	1.25	47.75	1.88	47.75	13.79	200	55.16	800	736.6	29	127	5	0.94	0.63	30.48	100
38.1	1.5	52.83	2.08	52.83	13.79	200	55.16	800	736.6	29	152.4	6	1.09	0.73	30.48	100
50.8	2	66.04	2.6	66.04	13.79	200	55.16	800	736.6	29	177.8	7	1.41	0.95	30.48	100
63.5	2.5	81.28	3.2	81.28	13.79	200	55.16	800	736.6	29	228.6	9	2.05	1.38	30.48	100
76.2	3	95.25	3.75	95.25	13.79	200	55.16	800	736.6	29	254	10	2.65	1.78	30.48	100

Temperature Rating: -40° F to 180° F

Static wire between tube and cover for grounding.

Safety. Value. Performance.

Lewis-Goetz is a one-stop solutions provider with local, on-the-shelf inventory to provide you with the highest level of oilfield service.

Goodall

LewisGoetz

An Erik's Company
ERIKS